SUDAS Revision Submittal Form

Status Date:	As of 5	5/20/2025	Topic:	Pipe size for clo	sed profile PVC pipe
Manual:	Specifi	cations	Manual Location:	Section 4010, 2	.01, D
Requested Revision:					
2.01 SANITARY SEWER (Gravity Mains)					
D. Closed Profile Polyvinyl Chloride Pipe (PVC) 21 inch to 36 60 inch:					
1. Comply with ASTM F 1803.					
2. Pipe stiffness per ASTM D 2412, 46 psi.					
3. PVC plastic meeting ASTM D 1784, Cell Classification 12364.					
4. Integral bell and spigot joints with elastomeric seals complying with ASTM D 3212 and ASTM F 477.					
Reason for Revision: Request from material supplier based on acceptance from ASTM.					
Comments:		None.			
Region:		Central	East		West
Comments: Add language in execution (flexible pipe) stating anything over 36 inch ne to be specified or per manufacturer's requirements.					ing over 36 inch needs
Action:		Deferred	Not A	Approved	Approved
Region:		Central	🖂 East		West
Comments:		None.			
Action:		Deferred	Not A	Approved 🛛	Approved
Region:		Central	East	\boxtimes	West
Comments:		None.			
Action:		Deferred	Not A	Approved 🛛 🖂	Approved

Final Regional Action Summary: All 3 regions approved; see comments above.

Board of Directors Action: Approved.